

# Product Details and Certifications

Cross Reference RA Part Number: DB!8 %&- ( \*

➔ Product: % \$; !; !9 LH

Description: 0æ ^EÖÖcc) áÁ^!{ ä æÄÚ| |EÜc ÁH



Representative Photo Only (actual product may vary based on configuration selections)

## CIRCUIT BREAKER DATA

|                   |                     |
|-------------------|---------------------|
| Bulletin Number   | Bulletin 140G/140MG |
| Frame Size        | G frame             |
| Rated Current(A)  | 125 A               |
| Ð~ { à^!Ä -ÁÚ   • | HÁÚ   •             |


## ACCESSORY ITEMS

|                  |                                  |
|------------------|----------------------------------|
| Öcc) á^áÁ^!{ ä æ | 0æ ^EÖÖcc) áÁ^!{ ä æÄÚ   EÜc ÁHÁ |
|------------------|----------------------------------|


## CERTIFICATIONS AND APPROVALS

|                                  |   |
|----------------------------------|---|
| UL                               | UL489   |
| CSA                              | CSA22.2 No. 5   |
| IEC                              | IEC 60947-2   |
| Certifications                   | UL Listed<br>CSA Certified<br>CE  |
| For UL Certifications Directory: | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> |


**Extended Terminals**

| <br>Representative Photo   | Description | Frame Size  | 3-Pole Cat. No.<br>(Pkg. Qty. 3) | 4-Pole Cat. No.<br>(Pkg. Qty. 4) |
|---|-------------|-------------|----------------------------------|----------------------------------|
|   |             |             | 140G-G-EXT3                      | 140G-G-EXT4                      |
| <b>Extended Terminals</b><br>for busbar or ring type connection<br>• G- & I-frame supplied with 100 mm phase barrier<br>• H- & J-frame supplied with insulator, 100 mm phase barrier, and terminal cover<br>• K- & N-/NS-frame supplied with insulator and 100 mm phase barrier<br>• M-frame terminals only | G           | 140G-G-EXT3 | 140G-G-EXT4                      |                                  |
|   | H           | 140G-H-EXT3 | 140G-H-EXT4                      |                                  |
|   | I           | 140G-I-EXT3 | 140G-I-EXT4                      |                                  |
|   | J           | 140G-J-EXT3 | 140G-J-EXT4                      |                                  |
|   | K           | 140G-K-EXT3 | 140G-K-EXT4                      |                                  |
|   | M           | 140G-M-EXT3 | 140G-M-EXT4                      |                                  |
|   | N, NS       | 140G-N-EXT3 | 140G-N-EXT4                      |                                  |

**Spreader Terminals**

| <br>Representative Photo  | Description  | Frame Size    | 3-Pole Cat. No.<br>(Pkg. Qty. 3) | 4-Pole Cat. No.<br>(Pkg. Qty. 4) |
|--|--|---------------|----------------------------------|----------------------------------|
|  |  |               | 140G-G-EXS3                      | 140G-G-EXS4                      |
| <b>Spreader Terminals</b><br>for busbar or ring type connection<br>• G- & I-frame supplied with 200 mm phase barrier<br>• H- & J-frame supplied with insulator, 100 mm phase barrier, and terminal cover<br>• K- & N-/NS-frame supplied with insulator and 100 mm phase barrier<br>• M- & R-frame terminals only | G  | 140G-G-EXS3   | 140G-G-EXS4                      |                                  |
|  | H  | 140G-H-EXS3   | 140G-H-EXS4                      |                                  |
|  | I  | 140G-I-EXS3   | 140G-I-EXS4                      |                                  |
|  | J  | 140G-J-EXS3   | 140G-J-EXS4                      |                                  |
|  | K  | 140G-K-EXS3   | 140G-K-EXS4                      |                                  |
|  | M  | —             | 140G-M-EXS4                      |                                  |
|  | N, NS  | —             | 140G-N-EXS4                      |                                  |
| <b>Top Spreader Terminals</b><br>for busbar or ring type connection<br>• M-frame terminals only  | M  | 140G-M-EXSLI3 | —                                |                                  |
|  | N, NS  | 140G-N-EXSLI3 | —                                |                                  |
|  | <b>Bottom Spreader Terminals</b><br>for busbar or ring type connection<br>• N-/NS-frame supplied with insulator and 100 mm phase barrier | M             | 140G-M-EXSLO3                    | —                                |
| N, NS  |  | 140G-N-EXSLO3 | —                                |                                  |

**Rear Terminals**

| <br>Representative Photo | Description                    | Frame Size                          | 3-Pole Cat. No.<br>(Pkg. Qty. 3) | 4-Pole Cat. No.<br>(Pkg. Qty. 4) |             |
|---|--------------------------------|-------------------------------------|----------------------------------|----------------------------------|-------------|
|   |                                |                                     | 140G-N-TLV3                      | 140G-N-TLV4                      |             |
| <b>Rear flat horizontal terminals</b>   | Rear flat horizontal terminals | N, NS                               | 140G-N-TLH3                      | 140G-N-TLH4                      |             |
|   |                                | <b>Rear flat vertical terminals</b> | N, NS                            | 140G-N-TLV3                      | 140G-N-TLV4 |
|   |                                |                                     | R ★                              | 140G-R-TLV3                      | 140G-R-TLV4 |

★ 2000 A and 2500 A MCCBs only.