

# Product Details and Certifications

**Cross Reference RA Part Number: 1492-EBL6T A**

 **Product: 1492-EBL6T**

Description: 1492 Terminal Block, End Barrier, Gray (Standard), Qty. 50



Representative Photo Only (actual product may vary based on configuration sections)

## ***ACCESSORY SELECTION***

---

Bulletin Number	1492 Terminal Block Accessories
Accessory Selection	Individual Accessory Selection

## ***SELECTION***

---

1492 Accessory

# Spring-Clamp Connection Terminal Blocks

## Standard Feed-Through Blocks

	1492-L6	1492-L6T	1492-L10
<p>Dimensions are not intended to be used for manufacturing purposes.  <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.</p>			
<b>Specifications</b>	<i>Feed-through terminal block</i>		<i>Feed-through terminal block with 2 connection points on one side</i>
<b>Certifications</b>	<b>CSA</b> <b>IEC</b> <b>ATEX</b>	<b>CSA</b> <b>IEC</b> <b>ATEX</b>	<b>CSA</b> <b>IEC</b> <b>ATEX</b>
<b>Voltage Rating</b>	600V AC/DC 800V AC/DC	600V AC/DC 800V AC/DC	600V AC/DC 550V AC/DC
<b>Maximum Current</b>	50 A 41 A 36 A	50 A 41 A 36 A	60 A 55 A 57 A 50 A
<b>Wire Range (Rated Cross Section)</b>	#22...8 AWG #20...8 AWG 6 mm <sup>2</sup>	#22...8 AWG #20...8 AWG 6 mm <sup>2</sup>	#20...8 AWG 6 mm <sup>2</sup> 6 mm <sup>2</sup> (#20...10 AWG) #16...6 AWG 10 mm <sup>2</sup> 10 mm <sup>2</sup> (16...8 AWG)
<b>Wire Strip Length</b>	0.51 in. (13 mm)		0.70 in. (18 mm)
<b>Density</b>	37 pcs/ft (123 pcs/m)		30 pcs/ft (99 pcs/m)
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)		
<b>Short-Circuit Current Rating</b>	See page 12-78		
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>
<b>Color</b>	<b>1492-L6</b>	50	<b>1492-L6T</b>
Grey	<b>1492-L6-RE</b>	50	<b>1492-L6T-RE</b>
Red	<b>1492-L6-B</b>	50	<b>1492-L6T-B</b>
Blue	<b>1492-L6-BL</b>	50	<b>1492-L6T-BL</b>
Black	<b>1492-L6-G</b>	50	<b>1492-L6T-G</b>
Green	<b>1492-L6-Y</b>	50	<b>1492-L6T-Y</b>
Yellow	<b>1492-L6-OR</b>	50	<b>1492-L6T-OR</b>
Orange	<b>1492-L6-BR</b>	50	<b>1492-L6T-BR</b>
Brown	<b>1492-L6-W</b>	50	<b>1492-L6T-W</b>
White	<b>1492-L10</b>	25	<b>1492-L10-RE</b>
Grey	<b>1492-L10-B</b>	25	<b>1492-L10-B</b>
Blue	<b>1492-L10-BL</b>	25	<b>1492-L10-BL</b>
Black	<b>1492-L10-G</b>	25	<b>1492-L10-G</b>
Green	<b>1492-L10-Y</b>	25	<b>1492-L10-Y</b>
Yellow	<b>1492-L10-OR</b>	25	<b>1492-L10-OR</b>
Orange	<b>1492-L10-BR</b>	25	<b>1492-L10-BR</b>
Brown	<b>1492-L10-W</b>	25	<b>1492-L10-W</b>
White	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>
<b>Accessories</b>	<b>1492-DR1</b>	10	<b>1492-DR1</b>
<b>Mounting Rails</b>	<b>1492-DR5</b>	10	<b>1492-DR5</b>
1 m Symmetrical DIN (Steel)	<b>1492-DR6</b>	2	<b>1492-DR6</b>
1 m Symmetrical DIN (Aluminum)	<b>1492-DR7</b>	2	<b>1492-DR7</b>
1 m Hi-Rise Sym. DIN (Aluminum)	<b>1492-EBL6</b>	50	<b>1492-EBL6T</b>
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-EBL6-B</b>	50	<b>1492-EBL6T-B</b>
<b>End Barriers</b>	<b>1492-EBL6-Y</b>	50	<b>1492-EBL6T-Y</b>
Grey	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>
Blue	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>
Yellow	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>
<b>End Anchors and Retainers</b>	<b>1492-CJL8-32</b>	10	<b>1492-CJL8-32</b>
<b>Screwless End Retainer</b>	<b>1492-CJL8-4</b>	60	<b>1492-CJL8-4</b>
<b>Jumpers</b>	<b>1492-CJL8-3</b>	60	<b>1492-CJL8-3</b>
Plug-in Center Jumper — 32-Pole	<b>1492-CJL8-2</b>	60	<b>1492-CJL8-2</b>
Plug-in Center Jumper — 4-Pole	—	—	—
Plug-in Center Jumper — 3-Pole	<b>1492-CJL10-2</b>	25	<b>1492-CJL10-2</b>
Plug-in Center Jumper — 2-Pole	—	—	—
<b>Other Accessories</b>	<b>1492-TPL8</b>	25	<b>1492-TPL8</b>
Test Plug	<b>1492-EWPL8</b>	20	<b>1492-EWPL8</b>
Test Plug (Stackable)	<b>1492-M6X12</b> (120/card)	5	<b>1492-M6X12</b> (120/card)
Electrical Warning Plate	<b>1492-M8X5</b> (160/card)	5	<b>1492-M8X5</b> (160/card)
Marking Systems	<b>1492-MH6X12</b> (80/card)	5	<b>1492-MH6X12</b> (80/card)
Snap-In Marker Cards*	<b>1492-MH5X15</b> (96/card)	5	<b>1492-MH5X15</b> (96/card)
Snap-In Marker Cards			
Hinged Marker Cards			

\* May only be mounted in terminal block corner marking positions.