

# Product Details and Certifications

**Cross Reference RA Part Number: 193-T1AB25 A**

 **Product: 193-T1AB25**

Description: T1 MCS Overload Relay, IEC, Bimetallic, 1.8-2.5A



Representative Photo Only (actual product may vary based on configuration sections)

## ***OVERLOAD DATA***

---

Bulletin Number	193-IEC Overload Relay
Overload Relay Type	Biometric
Full Load Current Range (A)	1.8-2.5A

## ***CONTACTOR DATA***

---

Phases	3 Phase
Separate Mounting	No

## ***CERTIFICATIONS AND APPROVALS***

---

UL  
IEC  
CSA  
CE

## IEC Overload Relays &amp; Modular Protection System

## Product Overview

## Overload Relays

Bulletin	193-ED	193-EE	193-EC1	193-EC2/EC3	193-EC5	193-EC4
Type	E1 Plus Electronic Overload Relay	E1 Plus Electronic Overload Relay	E3 Electronic Overload Relay	E3 Plus Electronic Overload Relay		E3 Plus Current Monitoring Relay
Rated Current (Range)	0.1...45 A	0.1...800 A	0.4...5000 A			
NEMA Operating Voltage, Nominal	—	600V	600V			
IEC Operating Voltage, Nominal	690V	690/1000V	690/1000V			
Overload Type	Electronic Overload	Electronic Overload	Microprocessor-Based			
Trip Class (Fixed)	10	—	—			
Trip Class (Adjustable)	—	10, 15, 20, 30	5...30		—	
Ambient Temperature Compensated	✓	✓	✓		—	
Reset Type	Manual Only	Automatic and Manual	Automatic and Manual			
Adjustment Range	5:1	5:1	5:1			
Phase Loss	3 s	3 s	Adjustable Delay			—
Ground (Earth) Fault	—	Optional	—	Sensitive	Sensitive	Sensitive
Overcurrent (Jam) Detection	—	Optional	✓	✓	✓	—
Stall Detection	—	—	✓	✓	✓	—
Underload Detection	—	—	✓	✓	✓	—
Current Imbalance	—	—	✓	✓	✓	—
PTC Thermistor Monitoring	—	Optional	—	✓	—	—
Warning Settings	—	—	✓	✓	✓	✓
N.C. Trip Contact	✓	✓	✓	✓	✓	✓
N.O. Alarm Contact	✓	✓	—	—	—	—
No. of Outputs	—	—	1	2	2	2
No. of Inputs	—	—	2	4	6	4
ODVA (DeviceNet) Conformance	—	Optional	✓	✓	✓	✓
Variable Frequency Drive (VFD) Compatible	—	—	✓	✓	✓	✓
Product Selection	Page 2-208	Page 2-208	Page 2-222	Page 2-222	Page 2-222	Page 2-222

2

## Overload Relays &amp; Modular Protection System

Bulletin	193-K	193-T1	825-P
Type	Bimetallic Overload Relay		Modular Protection System
Rated Current (Range)	0.1...12.5 A	0.1...90 A	0.5...5000 A
Operating Voltage, Nominal	600V		120...240V AC/DC, 24...48V DC
Overload Type	Bimetallic		Microprocessor based
Trip Class (Fixed)	10	10	—
Ambient Temperature Compensated	✓	✓	✓
Reset Type	Automatic and Manual	Automatic and Manual	Automatic and Manual
Adjustment Range	1.5:1	1.5:1	—
Phase Loss	Normal Sensing	Normal Sensing	Adjustable delay
N.C. Trip Contact	✓	✓	✓
N.O. Alarm Contact	✓	✓	✓
Variable Frequency Drive (VFD) Compatible	✓	✓	✓
Product Selection	Page 2-246	Page 2-249	Page 2-260

Bulletin 193-T1  
**Bimetallic Overload Relays**  
 Product Selection

Thermal Overload Relays



For Use With*	Setting Range [A]‡	Max. Back-up fuse [A]			Cat. No.
		gL/gG		UL Class K5	
		50 kA, 690V AC		5 kA, 600V AC	
		IEC/EN 60947-4-1 Coordination			
	Type 1	Type 2	UL 508		
100-C09...100-C23	0.1...0.16	50	—	1	193-T1AA16
	0.16...0.25	50	—	1	193-T1AA25
	0.25...0.40	50	2	1	193-T1AA40
	0.35...0.50	50	2	2	193-T1AA50
	0.45...0.63	50	2	2	193-T1AA63
	0.55...0.80	50	4	3	<b>193-T1AA80</b>
	0.75...1.0	50	4	3	193-T1AB10
	0.90...1.3	50	6	4	<b>193-T1AB13</b>
	1.1...1.6	50	6	5	<b>193-T1AB16</b>
	1.4...2.0	50	10	8	<b>193-T1AB20</b>
	<b>1.8...2.5</b>	<b>50</b>	<b>16</b>	<b>10</b>	<b>193-T1AB25</b>
	2.3...3.2	50	16	12	<b>193-T1AB32</b>
	2.9...4.0	50	16	15	<b>193-T1AB40</b>
	3.5...4.8	50	16	15	<b>193-T1AB48</b>
	4.5...6.3	50	20	20	<b>193-T1AB63</b>
	5.5...7.5	50	25	25	<b>193-T1AB75</b>
7.2...10	50	25	35	<b>193-T1AC10</b>	
9.0...12.5	50	35	50	<b>193-T1AC12</b>	
100-C12...100-C23	11.3...16	50	35	60	<b>193-T1AC16</b>
100-C16...100-C23	15...20	80	40	80	<b>193-T1AC20</b>
	17.5...21.5	80	50	80	<b>193-T1AC21</b>
100-C23	21...25	80	50	100	<b>193-T1AC25</b>
100-C30...100-C37	15...20	80	40	80	<b>193-T1BC20</b>
	17.5...21.5	80	50	80	<b>193-T1BC21</b>
	21...25	80	50	100	<b>193-T1BC25</b>
	24.5...30	100	63	100	<b>193-T1BC30</b>
	29...36	125	63	125	<b>193-T1BC36</b>
100-C37	33...38	125	63	150	<b>193-T1BC38</b>
100-C43	17...25	100	50	100	<b>193-T1CC25</b>
	24.5...36	125	80	125	193-T1CC36
	35...47	160	100	175	<b>193-T1CC47</b>
100-C60...100-C97	35...47	160	100	175	<b>193-T1DC47</b>
	45...60	200	125	250§	<b>193-T1DC60</b>
100-C72...100-C97	58...75	200	125	300§	<b>193-T1DC75</b>
100-C85...100-C97	72...90	250	160	350§	<b>193-T1DC90</b>
	35...47	160	100	175	193-T1DC47P
Separate mounting required (Panel-mounted device)	45...60	200	125	250§	<b>193-T1DC60P</b>
	58...75	200	125	300§	193-T1DC75P
	72...90	250	160	350§	193-T1DC90P



\* Bulletin 193-T1 overload relays shall not be used with 100-C09...100-C43 conventional DC coil-controlled contactors. Use electronic controlled DC coil versions.  
 ‡ To select the setting range for use in Y-Δ Starters, multiply the rated operating current of the motor by a factor of 0.58.  
 † For motors with service factor of 1.15 or greater, use motor nameplate full load current. For motors with service factor of 1.0, use 90% of the motor nameplate full load current.  
 § Max. Back-up fuse [A], UL Class K5, 10 kA, 600V AC

### Marking System

Uniform labeling materials for contactors, motor starting equipment, timing relays, and circuit breakers

	Description	Pkg. Quantity*	Cat. No.
	<b>Label Sheet</b> 105 self-adhesive paper labels each, 6 x 17 mm	10	100-FMS
	<b>Marking Tag Sheet</b> 160 perforated paper labels each, 6 x 17 mm, to be used with a transparent cover	10	100-FMP
	<b>Transparent Cover</b> To be used with marking tag sheets	100	100-FMC

\* Must be ordered in multiples of package quantities.

### Thermal Overload Relays








#### Main Circuits

Cat. No.		193-T1...	
Rated isolation voltage $U_i$		690V AC	
Rated impulse withstand voltage $U_{imp}$ (between main poles and between main poles and auxiliary circuits)		6kV AC	
Rated impulse withstand voltage $U_{imp}$ (between auxiliary circuits)		4kV AC	
Rated operating voltage $U_e$	IEC	690V AC	440V DC
	UL, CSA	600V AC	
Rated frequencies		[Hz]	50/60
Operational frequencies		DC...400 Hz	
Power dissipation	193-T1A, 193-T1B	up to 0.4 A	7 W
		0.5...36 A	6 W
		38 A	12 W
	193-T1C	25...47 A	12 W
	193-T1D	47...90 A	18 W

#### Control Circuits

Cat. No.		193-T1...	
Rated operating current $I_e$			
AC-15	24V	[A]	4
	240V	[A]	2
	400V	[A]	1.6
	690V	[A]	0.15
DC-13	24V	[A]	2
	110V	[A]	0.4
	220V	[A]	0.25
	440V	[A]	0.08
Thermal Current $I_{th}$		5	
Short-circuit withstand, Fuse	IEC, gL/gG	[A]	6
Short-circuit withstand, circuit breaker $\leq$ 1 kA prospective short-circuit-current		[A]	4
Min. contact load for reliable operation		15V, 2 mA	
UL Rating		A600/Q300	

### Terminations

Cat. Nos.	Main Circuits						Control Circuits	Remote Reset	
	193-T1A...	193-T1BC20... T1BC25	193-T1BC30... T1BC38	193-T1C...	193-T1D...	193-T1APM	193-T1... all	193-T1R...	
Wiring cross section Terminal type									
Terminal screws	M4	M4	M4	M5	M6	M4	M3.5	M3.5	
 Fine stranded with ferrule	1 conductor [mm <sup>2</sup> ]	1.5...4	1.5...4	2.5...10	2.5...16	10...35	1.5...10	1...2.5	
	2 conductors [mm <sup>2</sup> ]	1.5...4	1.5...4	-	-	-	-	-	
 Solid or coarse stranded	1 conductor [mm <sup>2</sup> ]	1.5...6	1.5...6	2.5...16	2.5...25	10...35	1.5...16	1...2.5	
	2 conductors [mm <sup>2</sup> ]	1.5...6	1.5...6	-	-	-	-	-	
 Solid or coarse stranded	1 conductor [AWG]	No. 16...10	No. 14...10	No. 10...6	No. 10...6	No. 8...1	No. 16...6	No. 18...12	
	2 conductors [AWG]	No. 16...10	No. 14...10	-	-	-	-	No. 18...12	
Recommended torque	[N•m]	1.5 ... 2.2	1.5 ... 2.2	2.5 ... 3.5	2.5 ... 3.5	4.5 ... 6	1.8...2.8	1.2	
	[lb•in]	13 ... 20	13 ... 20	22 ... 31	22 ... 31	40 ... 53	16...25	10.6	
Pozidrive screwdriver No.	Size	2	2	2	2	-	2	2	
Slotted screwdriver	[mm]	0.8 x 5.5	0.8 x 5.5	0.8 x 5.5	0.8 x 5.5	-	0.8 x 5.5	0.8 x 5.5	
Hexagon socket screw	Size	-	-	-	-	4	-	-	

## 193-T1R Remote Reset

Operating Limits		
Maximum Command Impulse		5s
AC 50/60 Hz	Pick-up [ $\times U_s$ ]	0.8...1.1
	Drop-out [ $\times U_s$ ]	
DC	Pick-up [ $\times U_s$ ]	0.7...1.25
	Drop-out [ $\times U_s$ ]	
Coil Consumption		
AC 50/60 Hz	Pick-up [VA/W]	
	Hold-in [VA/W]	
DC	Pick-up [W]	17 (24, 110, 125V) 25 (48V)
	Hold-in [W]	17 (24, 110, 125V) 25 (48V)

## General

Cat. No.		193-T1...	
Type of Overload Relay	Bimetallic, Ambient Compensated, Phase Loss Sensitive		
Trip Rating (ultimate tripping current)	120% FLA		
Phase loss sensitivity: Trip rating at phase loss	115% FLA		
Trip Class	IEC/EN 60947-4-1	193-T1A/-T1B	193-T1C/-T1D
	UL	10A	10
Reset Mode	Automatic or Manual		
Test release	Manual release of auxiliary contacts		
Trip indication	By means of a flag visible through an opening in the relay front		
Compensation temperature range	-20...+60 °C (-4...+140 °F)		
Climatic Conditions	Release Tolerance at -20 °C	1.05...1.4 $\times I_n$	
	Storage Temperature Range	-55...+80 °C (-67...+176 °F)	
	Operating Temperature Range	-20...+60 °C (-4...+140 °F)	
	Air moisture (Storage/Operating)	5...95% rel.humidity, non-condensing	
Vibration	(per IEC/EN 60068-2-6), service	3g	
	IEC/EN 61373 (vibration railways)	category 1, class B	
Shock	IEC/EN 60092-504 (vibration ships), service	0.7 g, all axes, 2...200 Hz	
	(per IEC/EN 68000-2-27), transport	30 g	
Shock	IEC/EN 60068-2-27 (Shock half-sinus), service	11 ms > 5 g all axes	
	IEC/EN 61373 (shock railways)	category 1, class B, 5g 30 ms	
Max. Altitude	2000 m		
Pollution Degree	3		
Degree of Protection, with wires connected	IP2X		
Approximate Weight (unpacked)	193-T1A, 193-T1B	0.16...25 A	0.115 kg
	193-T1B	30...38 A	0.155 kg
	193-T1C	25...47 A	0.330 kg
	193-T1D	47...90 A	0.360 kg
	193-T1...P	47...90 A	0.415 kg
Standards	IEC/EN 60497-1, -4-1, -5-1, UL508, CSA C22.2 No.14		
Certifications	CE, cULus		