

**CROSS REFERENCES TO ROCKWELL  
AUTOMATION 25107-447-01**

**Types LDB, HLDB and LDCB Electronic Circuit Breakers with Non-Interchangeable Electronic Trip Units Suitable for Reverse Feed**

Maximum Continuous Ampere Rating at 40°C	Short Time Range	Short Time Delay	Ground Fault Pickup	Number of Poles	Circuit Breaker Frame Including Digitrip RMS 310 Electronic Trip Unit Less Terminals and Rating Plug—Catalog Number				Digitrip RMS 310 Rating Plug (Order as Separate Items)	
					LS	LSI	LSG	LSIG	Fixed	Adjustable
					L – Adjustable Long Delay Pickup (By Adjustable Rating Plug)	S – Adjustable Short Delay Pickup with Fixed Short Delay Time (I <sup>2</sup> t Response) or Adjustable Short Time (Flat Response)	I – Adjustable Instantaneous Pickup by Setting Short Time Delay Time to Instantaneous	G – Adjustable Ground Fault Pickup with Adjustable Ground Fault Delay (Flat Response)		
					2–8 x I <sub>n</sub>	2–8 x I <sub>n</sub>	2–8 x I <sub>n</sub>	2–8 x I <sub>n</sub>		
					—	1–300 ms	—	0–300 ms		
					—	—	Varies by frame	Varies by frame		
					—	—	0–500 ms	0–500 ms		
									<b>Catalog Number</b>	
<b>Type LDB, HLDB and LDCB with Digitrip 310 Non-Interchangeable Trip Unit</b>										
600	3	LDB3600FT33W	LDB3600FT32W	LDB3600FT35W	LDB3600FT35W	6LES300T	300/400/500/600			
						6LES350T	A6LES600T1			
						6LES400T	420/440/460/480			
						6LES450T	A6LES400T5			
						6LES500T	520/540/560/580			
						6LES600T	A6LES500T5			
600	3	HLDB3600FT33W	HLDB3600FT32W	HLDB3600FT35W	HLDB3600FT36W	6LES300T	300/400/500/600			
						6LES350T	A6LES600T1			
						6LES400T	420/440/460/480			
						6LES450T	A6LES400T5			
						6LES500T	520/540/560/580			
						6LES600T	A6LES500T5			
600	3	LDCB3600FT33W	LDCB3600FT32W	LDCB3600FT35W	LDCB3600FT36W	6LES300T	300/400/500/600			
						6LES350T	A6LES600T1			
						6LES400T	420/440/460/480			
						6LES450T	A6LES400T5			
						6LES500T	520/540/560/580			
						6LES600T	A6LES500T5			

