



Cross Reference RA Part Number 40121-799-13

SERIES: Rockwell Automation *Allen-Bradley*

APPLICATIONS

- ◆ At the load within Motor Control Centers (MCCs)

STANDARD FEATURES

- ◆ UL recognized component
- ◆ 2-year warranty
- ◆ 3-line fusing
- ◆ Discharge resistors per NEC requirements
- ◆ Assembled in the USA



0.5 Space Factor Tray

STANDARD RATINGS

- ◆ 240, 480, 600 V
- ◆ 3-phase
- ◆ 60 Hz

CAPACITOR CELLS

- ◆ 20-year rated life
- ◆ 2-year warranty
- ◆ Self-contained, 3-phase, delta-connected
- ◆ Industrial grade dry-type construction
- ◆ Losses of less than ½ watt per kVAr
- ◆ Self-healing metallized polypropylene dielectric film
- ◆ 3-phase pressure-actuated interrupter
- ◆ Hermetically-sealed tin-plated steel case
- ◆ Threaded insulated terminals



1.0 Space Factor Tray

FUSES

- ◆ Fast-acting, current-limiting, with 200,000 ampere interrupting capacity

FIELD WIRING TERMINATION

- ◆ Mechanical connections are provided for all field wiring termination points
- ◆ Refer to product manual for incoming conductor information

TWO MODELS AVAILABLE

- ◆ TANM: blown fuse indication
- ◆ TAPM: fusing without indication


OPTIONS

- ◆ Other voltages and frequencies available
- ◆ Other kVAr configurations available


MYRON ZUCKER TRAYMOUNT® Brand Capacitor Series

TRAY DESIGN	CONFIGURATION	MAXIMUM kVAr			APPROX. DIMENSIONS		
		240 V	480 V	600 V	H	W	D
Rockwell Automation <i>Allen-Bradley</i>	0.5 Space Factor	16.0	40.0	35.0	4.50	14.25	7.75
	1.0 Space Factor	25.0	60.0	60.0	8.75	15.50	8.25

All dimensions are in inches. We reserve the right to change dimensions without notice.

FUSING INDICATION	PLEASE INSERT:
With Blown Fusing Indication	N
 Without Indication	P

SELECTION CHART

240 V / 3Ø / 60 Hz			480 V / 3Ø / 60 Hz			600 V / 3Ø / 60 Hz		
kVAr	PART NUMBER	AMPS*	kVAr	PART NUMBER	AMPS*	kVAr	PART NUMBER	AMPS*
1	TA_M23001-3	2.4	1	TA_M43001-3	1.2			
1.5	TA_M23001X-3	3.6	1.5	TA_M43001X-3	1.8			
2	TA_M23002-3	4.8	2	TA_M43002-3	2.4	2	TA_M63002-3	1.9
2.5	TA_M23002X-3	6.0	2.5	TA_M43002X-3	3.0	2.5	TA_M63002X-3	2.4
3	TA_M23003-3	7.2	3	TA_M43003-3	3.6	3	TA_M63003-3	2.9
4	TA_M23004-3	9.6	4	TA_M43004-3	4.8	4	TA_M63004-3	3.8
5	TA_M23005-3	12	5	TA_M43005-3	6.0	5	TA_M63005-3	4.8
6	TA_M23006-3	14	6	TA_M43006-3	7.2	6	TA_M63006-3	5.8
7.5	TA_M23007X-3	18	7.5	TA_M43007X-3	9.0	7.5	TA_M63007X-3	7.2
10	TA_M23010-3	24	10	TA_M43010-3	12	10	TA_M63010-3	9.6
12.5	TA_M23012X-3	 12.5	12.5	TA_M43012X-3	15	12.5	TA_M63012X-3	12
15	TA_M23015-3	36	15	TA_M43015-3	18	15	TA_M63015-3	14
16	TA_M23016-3	38	16	TA_M43016-3	19	16	TA_M63016-3	15
17.5	TA_M23017X-3	42	17.5	TA_M43017X-3	21	17.5	TA_M63017X-3	16
20	TA_M23020-3	48	20	TA_M43020-3	24	20	TA_M63020-3	19
22.5	TA_M23022X-3	54	22.5	TA_M43022X-3	27	22.5	TA_M63022X-3	22
25	TA_M23025-3	60	25	TA_M43025-3	30	25	TA_M63025-3	24
			27.5	TA_M43027X-3	33	27.5	TA_M63027X-3	26
			30	TA_M43030-3	36	30	TA_M63030-3	29
			32.5	TA_M43032X-3	39	32.5	TA_M63032X-3	31
			35	TA_M43035-3	42	35	TA_M63035-3	34
			37.5	TA_M43037X-3	45	37.5	TA_M63037X-3	36
			40	TA_M43040-3	48	40	TA_M63040-3	38
			42.5	TA_M43042X-3	51	42.5	TA_M63042X-3	41
			45	TA_M43045-3	54	45	TA_M63045-3	43
			50	TA_M43050-3	60	50	TA_M63050-3	48
			60	TA_M43060-3	72	60	TA_M63060-3	58

Complete part number by inserting indication preference.

Ex. TANM43010-3: Myron Zucker, Inc. Rockwell Automation *Allen-Bradley* Design with blown fuse indication.