

Product Details and Certifications

Cross Reference RA Part Number: 800F-N5G A

➔ Product: **800F-N5G**

Description: Integrated LED, Latch Mount, 120V AC, Green LED



Representative Photo Only (actual product may vary based on configuration selections)

POWER MODULE DATA

Latch Style	Latch Mount
Power Module Type	Integrated LED
Voltage	120V AC
Lamp Type	Green LED
Packaging	Standard Pack, Quantity:10

CERTIFICATIONS AND APPROVALS

UR

CSA

CE

CCC

For UL Certifications Directory:

<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

Bulletin 800FC
22.5 mm Configured Pendant Stations
 Accessories

	Description	Pkg. Quantity	Cat. No.
	Plastic mounting latch	10	800F-ALP
	Mechanical interlock latch	1	* 800FC-ALP
	Replacement wire guide †	10	800FC-AWG
	Replacement trim washer	10	800F-ATW1
	Insulated side jumper	50	1492-SJ5A-24
			1492-SJ5A-10
	Hole plug	1	800F-N2
	Contact block	10	Description
			Type
			N.O.
			N.C.
			N.O. low voltage — QuadCONNECT™
			N.C. low voltage — QuadCONNECT™
			N.C.E.B.
			NOEM* ‡
NOEM ‡			
NOEEM †	‡	800F-X10M	
	Cable sleeve	1	3-hole (M20 x 1.5)
			5-...9-hole (M32 x 1.5)
	Protective boot	10	Extended push button
			2-position multi-operator
	Narrow plastic guard	1	Yellow
			800F-AMEGY
	Integrated LED module	10	24V AC/DC
			120V AC
			§ 800F-N3x
			§ 800F-N5x ←

- * Only for use with 1-, 2-, and 3-speed operators.
- * First contact closure of 1- and 2-speed operators.
- ‡ Second contact closure of 2-speed operators and third contact closure of 3-speed operators.
- ‡ First contact closure of 3-speed operators.
- * For proper operation, **Cat. No. 800F-X10M** must be mounted in position 3 of the mechanical or standard latch.
- ‡ Not for use with 1-, 2-, and 3-speed operators.
- § To complete the cat. no., replace the x with one of the following letters for the desired color: Y = Amber, R = Red, **G = Green**, B = Blue, W = White.
- † Wire guides are provided with enclosures.



10