


Limitron® Quick-Acting Fuses

Class J – 600 Volt

JKS
1-60A



Dimensional Data



General Information:

- Single-element, current-limiting fuses provide superior short-circuit protection.
- Protects low interrupting capacity circuit breakers. Limits the short-circuit current to meet the interrupting capacity requirements of existing equipment.
- On older systems available short-circuit current may exceed the interrupting capacity of the circuit breakers, fuses can be installed in series with existing equipment.
- Well suited for lighting and heating circuits and other non-inductive loads.
- Provides component short-circuit protection in compliance with NEC 110-10, where protection devices shall clear a fault without "extensive damage" to the circuit components.
- High interrupting rating helps meet the requirements of future system expansion and the increases in available utility short-circuit current.
- Fuses can be selectively coordinated with ease.

Catalog Symbol: JKS

Quick-Acting

Current-Limiting

Ampere Rating: 1 to 60A

Voltage Rating: 600Vac (or less)*

Interrupting Rating: 200,000A RMS Sym.

Agency Information:

UL Listed, Std. 248-8, Class J, Guide JDDZ, File E4273

CSA Certified, C22.2 No. 248.8, Class 1422-02, File 53787

Catalog Numbers

JKS-1	JKS-8	JKS-30
JKS-2	JKS-10	JKS-35
JKS-3	JKS-12	JKS-40
JKS-4	JKS-15	JKS-45
JKS-5	JKS-20	JKS-50
JKS-6	JKS-25	JKS-60




Carton Quantity and Weight

Amps	Carton Qty.	Weight**	
		Lbs.	Kg.
1-30	10	0.95	0.430
35-60	10	1.175	0.532

*15-30A rated 200VDC, 31-60A rated 175VDC and 10 KAIC.

**Weight per carton.

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 314-527-1270 for more information.



Recommended fuseblocks/fuseholders for Class J 600V fuses
See Data Sheets listed below

- Finger-safe fuseholders - 1152
- Open fuseblocks - 1114
- Open pyramid fuseblocks - 1108


Limitron® Quick-Acting Fuses

Class J – 600 Volt


JKS

1-60A

Current Limitation Curves



Time-Current Characteristic Curves-Average Melt



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.