

LIMITRON®

Fast-Acting Fuses

13/32" x 1-1/2", Class CC - 600 Volt, 1/10 - 30 Amps



Dimensional Data



Catalog Symbol: KTK-R
Fast-Acting Branch Circuit Fuse:

1/10 TO 30A

Voltage Rating:

600Vac (or less): 0-30A

Interrupting Rating:

ac: 200,000A RMS Sym.

UL Listed, STD. 248-4, Class CC,

(Guide #JDDZ, File #E4273)

CSA Certified, C22.2 NO. 248.4, (File #53787—Class #1422-02)

Electrical Ratings (Catalog Symbol and Amperes)

600Vac - UL Listed & C.S.A.

KTK-R-1/10	KTK-R-6/10	KTK-R-3-1/2	KTK-R-10
KTK-R-1/8	KTK-R-3/4	KTK-R-4	KTK-R-12
KTK-R-2/10	KTK-R-1	KTK-R-5	KTK-R-15
KTK-R-1/4	KTK-R-1-1/2	KTK-R-6	KTK-R-20
KTK-R-3/10	KTK-R-2	KTK-R-7	KTK-R-25
KTK-R-4/10	KTK-R-2-1/2	KTK-R-8	KTK-R-30
KTK-R-1/2	KTK-R-3	KTK-R-9	-

Carton Quantity and Weight

Ampere Ratings	Carton Qty.	Weight*	
		Lbs.	Kg.
1/10-30	10	.180	.082

*Weight per carton.

Recommended fuseblocks/fuseholders for Class CC 600V fuses
 See Data Sheets listed below

- Open fuseblocks - 1105
- Finger-safe fuseholders - 1109, 1102, 1103, 1151
- Panel-mount fuseholders - 2114, 2113
- In-line fuseholders - 2126

- LIMITRON® fast-acting fuse.
- Melamine tube. Nickel-plated brass endcaps.
- U.L. Listed for branch circuit protection.
- Rejection type; for both standard holders or those which reject other type fuses.

Time-Current Characteristic Curves—Average Melt



CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this Data Sheet are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.